



- Municipal
- Commercial
- Government

Turn-key solutions to control traffic patterns, parking enforcement and site security



800•642•7289

Copyright © 2001

CS36-FM-HD 3'-0"

Flush Mount Directional Traffic Controller

- **Prevents Wrong Way Traffic Or Unauthorized Exits**
- **Controls All Pneumatic Tires Including Steel Belts**
- **Smooth Flow In Free Direction**
- **Ramp Height 2.0 Inches (Teeth Down)**
- **Install in Existing Commercial Driveways**
- **Any Width Driveway Can Be Controlled**
- **Non-Penetrating Configuration Available**



POSITIVE UNATTENDED ONE WAY TRAFFIC CONTROL

The model CS36 Surface Mount Heavy Duty Traffic Controller can be quickly attached to existing or new driveways (asphalt or cement) for commercial areas. Installing units end to end can control any width driveway. Because the CS36 is all above grade, drainage problems are minimal. The CS36 is fabricated from 3/8" steel plate and will carry the standard highway axle load expected in normal commerce.

LATCH DOWN: (Standard On ALL Units) For locations where it is desired to occasionally deactivate the controller, the CS36 is equipped with a latch down capabilities. The latch down permits the operator to lock the teeth in the down position to allow free flow in either direction. Using a key only a few seconds per module is required to lock or unlock the teeth.

FINISH: Powder Coated finish. Please Specify either (RED or YELLOW)

TEETH AND SPRINGS: Hot Dipped Galvanized

WEIGHT WITH PACKAGING: 115 LBS, Length 36" X Width 22" X Height 2"

ACCESSORIES: Illuminated warning signs, Non-illuminated warning signs, Heavy Duty Frames for oversized and weight vehicles and Complete Hot Dipped Galvanizing